

Three Phase String Inverter

SUN-4/5/6/7/8/10/12/15K-G06P3-EU-AM2-P1



2 MPP trackers, Max. efficiency up to 98.5%



Zero export application, VSG application



String intelligent monitoring (optional)



Wide output voltage range



Anti-PID function (Optional)

Deye

Stock Code: 605117.SH

Model	SUN-4K-G06P3 -EU-AM2-P1	SUN-5K-G06P3 -EU-AM2-P1	SUN-6K-G06P3 -EU-AM2-P1	SUN-7K-G06P3 -EU-AM2-P1	SUN-8K-G06P3 -EU-AM2-P1	SUN-10K-G06P3 -EU-AM2-P1	SUN-12K-G06P3 -EU-AM2-P1	SUN-15K-G06P3 -EU-AM2-P1
Input Side								
Max. DC Input Power (kW)	5.2	6.5	7.8	9.1	10.4	13	15.6	19.5
Max. DC Input Voltage (V)	1100							
Start-up DC Input Voltage (V)	140							
MPPT Operating Range (V)	120-1000							
Max. DC Input Current (A)	13+13							13+26
Max. Short Circuit Current (A)	19.5+19.5							19.5+39
No.of MPP Trackers	2							
No.of Strings per MPP Tracker	1							1+2
Output Side								
Rated Output Power (kW)	4	5	6	7	8	10	12	15
Max. Active Power (kW)	4.4	5.5	6.6	7.7	8.8	11	13.2	16.5
Nominal Output Voltage / Range (V)	3L/N/PE 220/380V, 230/400V							
Rated Grid Frequency (Hz)	50 / 60 (Optional)							
Operating Phase	Three phase							
Rated AC Grid Output Current (A)	6.1/5.8	7.6/7.3	9.1/8.7	10.7/10.2	12.2/11.6	15.2/14.5	18.2/17.4	22.8/21.8
Max. AC Output Current (A)	6.7/6.4	8.4/8	10/9.6	11.7/11.2	13.4/12.8	16.7/16	20/19.2	25/24
Output Power Factor	0.8 leading to 0.8 lagging							
Grid Current THD	<3%							
DC Injection Current (mA)	<0.5%							
Grid Frequency Range	47-52 or 57-62 (Optional)							
Efficiency								
Max. Efficiency	98.1%	98.2%			98.3%			98.5%
Euro Efficiency	97.5%							
MPPT Efficiency	>99%							
Protection								
DC Reverse-Polarity Protection	Yes							
AC Short Circuit Protection	Yes							
AC Output Overcurrent Protection	Yes							
Output Overvoltage Protection	Yes							
Insulation Resistance Protection	Yes							
Ground Fault Monitoring	Yes							
Anti-islanding Protection	Yes							
Temperature Protection	Yes							
Integrated DC Switch	Yes							
Remote software upload	Yes							
Remote change of operating parameters	Yes							
Surge protection	DC Type II / AC Type II							
General Data								
Size (mm)	283W×463H×178D							
Weight (kg)	11							
Topology	Transformerless							
Internal Consumption	<1W (Night)							
Running Temperature	-25-60°C, >45°C derating							
Ingress Protection	IP65							
Noise Emission (Typical)	<45 dB							
Cooling Concept	Natural cooling							Smart cooling
Max. Operating Altitude Without Derating	2000m							
Warranty	5 years							
Grid Connection Standard	VDE4105, IEC61727/62116, VDE0126, AS4777.2, CEI 0 21, EN50549-1, G98, G99, C10-11, UNE217002, NBR16149/NBR16150							
Operating Surroundings Humidity	0-100%							
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2							
Features								
DC Connection	MC-4 mateable							
AC Connection	IP65 rated plug							
Display	LCD1602							
Interface	RS485/RS232/Wifi/LAN							