



Main

Product or component type	Switch
Device application	Control
Load type	Inductive Resistive Fluorescent lamp Incandescent lamp
Colour tint	White

Complementary

Device presentation	Complete product
Rated current	16 AX at 250 V AC 50/60 Hz
Switch function	1-pole 2-way
Number of gangs	1 gang
Number of rocker	1
Clamping connection capacity	3 x 2.5 mm ² for solid cable(s) 3 x 2.5 mm ² for stranded cable(s) 4 x 1.5 mm ² for solid cable(s) 4 x 1.5 mm ² for stranded cable(s)
Connections - terminals	Brass terminal
Local signalling	Off: LED indicator, LED (amber)
Material	Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator
Device mounting	Surface Flush
Width	86 Mm
Height	86 Mm
Depth	34,2 Mm

Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	45 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant
Operating altitude	2000 m
Standards	BS EN 60669-1 IEC 60669-1 SS 227-1 MS IEC 60669-1

Đơn vị đóng gói

Trọng lượng Gói hàng 1	81,000 G
Chiều cao Gói hàng 1	34,000 Mm
Chiều rộng Gói hàng 1	86,000 Mm
Chiều dài Gói hàng 1	86,000 Mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Product Life Status : **Commercialised**