



### Main

Product or component type	Switch
Device application	Control
Load type	Fluorescent lamps Serial boost load (SBL) Resistive Small motor load Incandescent lamp
Colour tint	White

### Complementary

Device presentation	Complete product
Rated current	32 A at 250 V AC 50/60 Hz
Switch function	2-pole 1-way
Number of gangs	1 gang
Number of rocker	1
Clamping connection capacity	4 x 4 mm <sup>2</sup> for stranded cable(s) 1 x 10 mm <sup>2</sup> for stranded cable(s) 1 x 16 mm <sup>2</sup> for stranded cable(s)
Connections - terminals	Brass terminal
Local signalling	On: LED indicator, LED (amber)
Material	Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator
Device mounting	Flush
Width	86 Mm
Height	86 Mm
Depth	32 Mm

### Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	45 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant
Operating altitude	2000 m
Standards	BS EN 60669-1 SS 227-1 MS IEC 60669-1 IEC 60669-1

### Đơn vị đóng gói

Trọng lượng Gói hàng 1	153,000 G
Chiều cao Gói hàng 1	32,000 Mm
Chiều rộng Gói hàng 1	86,000 Mm
Chiều dài Gói hàng 1	86,000 Mm

### Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

Product Life Status : **Commercialised**