



Main

Product or component type	Switch
Device application	Control
Load type	Resistive Incandescent lamp Small motor load Serial boost load (SBL) Fluorescent lamps
Colour tint	White

Complementary

Device presentation	Complete product
Rated current	45 A at 250 V AC 50/60 Hz
Switch function	2-pole 1-way
Number of gangs	1 gang
Number of rocker	1
Clamping connection capacity	4 x 4 mm ² for stranded cable(s) 1 x 10 mm ² for stranded cable(s) 1 x 16 mm ² for stranded cable(s)
Connections - terminals	Brass terminal
Local signalling	On: LED indicator, LED (amber)
Material	Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator
Device mounting	Flush
Width	86 Mm
Height	86 Mm
Depth	32 Mm

Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	45 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant
Operating altitude	2000 m
Standards	MS IEC 60669-1 BS EN 60669-1 IEC 60669-1 SS 227-1

Đơn vị đóng gói

Trọng lượng Gói hàng 1	153,000 G
Chiều cao Gói hàng 1	32,000 Mm
Chiều rộng Gói hàng 1	86,000 Mm
Chiều dài Gói hàng 1	86,000 Mm

Product Life Status : **Commercialised**