



### Main

Range	AvatarOn
Product or component type	Time delay switch
Device presentation	Complete product

### Complementary

Device mounting	Flush
Number of gangs	1 gang
Number of rocker	1
Actuator	Rocker
Fixing mode	Clip-in
Colour tint	White
Surface finish	Glossy
[Ie] rated operational current	Resistive: 4 A Inductive: 4 A
[Ue] rated operational voltage	250 V AC 50...60 Hz
Clamping connection capacity	1...4 mm <sup>2</sup> for rigid cable(s) 1...4 mm <sup>2</sup> for stranded cable(s) 1...4 mm <sup>2</sup> for flexible cable(s)
Wire stripping length	12 Mm
Material	PC (polycarbonate): base PC (polycarbonate): base cover PC (polycarbonate): grid plate PC (polycarbonate): surround PC (polycarbonate): dolly Brass: terminal cover
Height	86 Mm
Width	86 Mm
Depth	34 Mm
Embedding depth	25 Mm
Net weight	0,077 Kg

### Environment

IP degree of protection	IP20
-------------------------	------

### Đơn vị đóng gói

Trọng lượng Gói hàng 1	77,000 G
Chiều cao Gói hàng 1	34,000 Mm
Chiều rộng Gói hàng 1	86,000 Mm
Chiều dài Gói hàng 1	86,000 Mm

Offer Sustainability

EU RoHS Directive

Under investigation

Product Life Status : **Commercialised**