



Main

Range	AvatarOn
Product or component type	Time delay switch
Device presentation	Complete product

Complementary

Device mounting	Flush
Number of gangs	2 gangs
Number of rocker	2
Actuator	Rocker
Fixing mode	Clip-in
Colour tint	White
Surface finish	Glossy
[Ie] rated operational current	Resistive: 4 A Inductive: 4 A
[Ue] rated operational voltage	250 V AC 50...60 Hz
Clamping connection capacity	1...4 mm ² for rigid cable(s) 1...4 mm ² for stranded cable(s) 1...4 mm ² for flexible cable(s)
Wire stripping length	12 Mm
Material	PC (polycarbonate): base PC (polycarbonate): base cover PC (polycarbonate): grid plate PC (polycarbonate): surround PC (polycarbonate): dolly Brass: terminal cover
Height	86 Mm
Width	86 Mm
Depth	34 Mm
Embedding depth	25 Mm
Net weight	0,089 Kg

Environment

IP degree of protection	IP20
-------------------------	------

Đơn vị đóng gói

Trọng lượng Gói hàng 1	78,000 G
Chiều cao Gói hàng 1	34,000 Mm
Chiều rộng Gói hàng 1	86,000 Mm
Chiều dài Gói hàng 1	86,000 Mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Product Life Status : **Commercialised**