



Main

Range	AvatarOn
Device application	Control
Product or component type	Switch
Number of gangs	2 gangs
Colour tint	White

Complementary

Device presentation	Complete product
Device mounting	Flush
Switch function	Curtain
Clamping connection capacity	2 x 2.5 mm ² for solid cable(s) 2 x 2.5 mm ² for stranded cable(s) 3 x 1.5 mm ² for solid cable(s) 3 x 1.5 mm ² for stranded cable(s)
Rated current	10 A at 250 V AC 50/60 Hz
Material	Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame
Load type	Inductive Resistive Fluorescent lamp Incandescent lamp
Connections - terminals	Brass terminal
Embedding depth	22,3 Mm
Width	86 Mm
Height	86 Mm
Depth	32 Mm

Environment

Maximum ambient air temperature for operation	35 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant
Operating altitude	2000
Standards	GB 16915.1
IP degree of protection	IP20

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Đơn vị đóng gói

Trọng lượng Gói hàng 1	70,000 G
Chiều cao Gói hàng 1	34,000 Mm
Chiều rộng Gói hàng 1	86,000 Mm
Chiều dài Gói hàng 1	86,000 Mm

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

Product Life Status : **Commercialised**