



Main

| | |
|---------------------------|-------------|
| Product or component type | Push-button |
| Device application | Doorbell |
| Colour tint | White |

Complementary

| | |
|------------------------------|--|
| Device presentation | Complete product |
| Rated current | 10 A at 250 V AC 50/60 Hz |
| Number of gangs | 1 gang |
| Number of rocker | 1 |
| Clamping connection capacity | 3 x 2.5 mm ² for solid cable(s) 3 x 2.5 mm ² for stranded cable(s) 4 x 1.5 mm ² for solid cable(s) 4 x 1.5 mm ² for stranded cable(s) |
| Connections - terminals | Brass terminal |
| Material | Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator |
| Marking | Bell symbol |
| Device mounting | Surface Flush |
| Width | 86 Mm |
| Height | 86 Mm |
| Depth | 34,2 Mm |

Environment

| | |
|---|--|
| IP degree of protection | IP20 |
| Maximum ambient air temperature for operation | 45 °C |
| Relative humidity | 0...95 % |
| Environmental characteristic | UV resistant |
| Operating altitude | 2000 m |
| Standards | MS IEC 60669-1 BS EN 60669-1 SS 227-1 IEC 60669-1 |

Đơn vị đóng gói

| | |
|------------------------|-----------|
| Trọng lượng Gói hàng 1 | 77,000 G |
| Chiều cao Gói hàng 1 | 34,000 Mm |
| Chiều rộng Gói hàng 1 | 86,000 Mm |
| Chiều dài Gói hàng 1 | 86,000 Mm |

Offer Sustainability

| | |
|-------------------|---------------------|
| EU RoHS Directive | Under investigation |
|-------------------|---------------------|

Product Life Status : **Commercialised**