



# **Tornado T2**

# Tornado T2 15W CDL E27 220-240V 1PF/6

Tornado has outstanding brightness which makes your colors appear more Vivid. It fits everywhere due to its compact design With comprehensive product range, it allows easy replacement of incandescent lamps all the way

### **Warnings and Safety**

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

#### **Product data**

General Information	
Cap-Base	E27 [ E27]
Nominal Lifetime (Nom)	10000 h
Switching Cycle	10000X
Rated Lifetime (Hours)	10000 h
Light Technical	
Color Code	865 [ CCT of 6500K]
Luminous Flux (Nom)	900 lm
Luminous Flux (Rated) (Nom)	900 lm
Color Designation	Cool Daylight
Lumen Maintenance 2000 h (Nom)	88 %
Chromaticity Coordinate X (Nom)	313
Chromaticity Coordinate Y (Nom)	337
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	61 lm/W
Color Rendering Index (Nom)	80

LLMF At End Of Nominal Lifetime (Nom)	65 %		
Operating and Electrical			
Input Frequency	50 or 60 Hz		
Power (Nom)	15.0 W		
Lamp Current (Nom)	110 mA		
Starting Time (Nom)	0.3 s		
Warm Up Time to 60% Light (Min)	5 s		
Warm Up Time to 60% Light (Max)	40 s		
Power Factor (Nom)	0.6		
Voltage (Nom)	220-240 V		
Controls and Dimming			
Dimmable	No		

Datasheet, 2021, August 25 data subject to change

# **Tornado T2**


Mechanical and Housing	
Bulb Shape	Spiral
Approval and Application	
Approval and Application	
Mercury (Hg) Content (Max)	2.0 mg
Mercury (Hg) Content (Nom)	1.5 mg
Energy Consumption kWh/1000 h	15 kWh
Product Data	

872790092584500

Order product name	Tornado T2 15W CDL E27 220-240V 1PF/6
EAN/UPC - Product	8727900925845
Order code	929689114802
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929689114802
Net Weight (Piece)	0.054 kg

## Dimensional drawing

Full product code



QSPIR-F Erp 15W/865 E27 220-240V 50/60Hz

Product	D (max)	C (max)	F (max)
Tornado T2 15W CDL E27 220-240V 1PF/6	51.5 mm	107.5 mm	42.5 mm

