



Pulse Start Metal Halide Standard

MS400/U/PS 6PK

Philips Pulse Start Metal Halide Lamps offer an optimized metal halide system for greater efficiency and lumen maintenance.

Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)

Product data

General Information	
Cap base	E39 [Single Contact Mogul Screw]
Operating position	UNIVERSAL [Any or Universal (U)]
Main application	General Lighting (G)
Life to 50% failures (nom.)	20000 h
ANSI code HID	M155/M135/E
Features	na [Not Applicable]
System description	Pulse Start
Light Technical	
Colour Code	640 [CCT of 4,000 K]
Luminous flux (rated) (nom.)	40000 lm
Colour designation	Cool White (CW)
Design mean lumens	30000 lm
Chromaticity coordinate X (nom.)	385
Chromaticity coordinate Y (nom.)	390

Correlated Colour Temperature (Nom)	4000 K
Luminous efficacy (rated) (nom.)	90 lm/W
Colour rendering index (nom.)	65
Operating and Electrical	
Lamp current (nom.)	3.25 A
Ignition supply voltage (min.)	254 V
Re-ignition time (min.) (max.)	10 min
Ignition time (max.)	120 s
Voltage (Max)	150 V
Voltage (Min)	120 V
Voltage (Nom)	135 V
Mechanical and Housing	
Lamp Finish	Clear
Cap-base information	Nic/Brass

Pulse Start Metal Halide Standard

Bulb material	Hard Glass
Bulb shape	ED-37

Approval and Application

Mercury (Hg) content (max.)	42.0 mg
-----------------------------	---------

UV

PET (NIOSH) (nom.)	10.4 h/500lx
Damage factor D/fc (nom.)	0.76

Luminaire Design Requirements


Bulb temperature (max.)	400 °C
-------------------------	--------

Cap-base temperature (max.)	210 °C
-----------------------------	--------

Product Data

Order product name	MS400/U/PS 6PK
EAN/UPC – product	046677232832
Order code	928601179001
SAP numerator – quantity per pack	1
Numerator – packs per outer box	6
SAP material	928601179001
SAP net weight (piece)	1.000 g

Dimensional drawing



MH PS 400W/640 E39 ED37 CL U

Product	D	C (max)
MS400/U/PS 6PK	4.625 in	11.5 in

