



# Essential SmartBright G4 LED Floodlight BVP150

## BVP150 LED63/WW PSU 70W SWB G2 GM

Essential SmartBright G4 LED Floodlight BVP150 - 6300 lm - 70 W - 3000 K

The Essential SmartBright G4 LED floodlight comes in a compact and sturdy design. Lightweight, with a robust die-cast aluminum housing and corrosion-proof coating, it's suitable for general outdoor applications. Plus, with a higher efficacy than the previous generation, it also saves more energy.

### Product data

General Information		Power Factor (Min)	
Light source color	830 warm white		0.9
Driver included	Yes	Controls and Dimming	
Optical cover/lens type	Glass	Dimmable	No
Control interface	-	Mechanical and Housing	
Connection	Flying leads/wires	Housing Material	Aluminum die-cast
Cable	Cable 0.6 m without plug	Optical cover/lens material	Glass
Protection class IEC	Safety class I	Overall length	276 mm
CE mark	-	Overall width	217 mm
		Overall height	31 mm
Operating and Electrical		Effective projected area	0.032 m <sup>2</sup>
Input Voltage	220-240 V	Color	Black
Input Frequency	50 or 60 Hz		
Inrush current	1.35 A		

# Essential SmartBright G4 LED Floodlight BVP150

## Approval and Application

Ingress protection code	IP65 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [ 1 J]

## Initial Performance (IEC Compliant)


Initial luminous flux (system flux)	6300 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	90 lm/W
Init. Corr. Color Temperature	3000 K
Initial chromaticity	(0.440, 0.403) SDCM <6
Initial input power	70 W
Power consumption tolerance	+/-10%

## Application Conditions


Ambient temperature range	-40 to +50 °C
---------------------------	---------------

## Product Data

Full product code	871951453264999
Order product name	BVP150 LED63/WW PSU 70W SWB G2 GM
EAN/UPC - Product	8719514532649
Order code	911401815283
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401815283
Net Weight (Piece)	1.000 kg



## Dimensional drawing



BVP150								
	10W	20W	30W	50W	70W	100W	150W	200W
A	107	141	188	220	273	320	382	454
B	99	122	155	175	202	246	289	331
C	29	27	28	30	33	37	39	40
a	45	75	100	125	125	160	200	250
b	5	5	6	8,5	8,5	8,5	8,5	10,5
c	5,5	5,5	6,5	9	9	9	9	11

## Floodlight surface LED

