



Main

Range	Mureva
Range of product	Mureva lights
Product name	Floodlight
Product or component type	Lamp
Device application	Ware-houses and parking garages Residential Media device support Public areas Secure lighting Stadiums and arenas

Complementary

Type of installation	Outdoor
Total system power	20 W
Light source	LED
[Ue] rated operational voltage	230 V AC
Power factor	0.9
Colour rendering index	Ra=80
Luminous flux	2000 lm
Bulb lifespan	50000 h
Colour temperature	4000 K
Colour	Black
Provided equipment	Sensor
Beam angle	110 °
Shape	Rectangular
Height	163.4 mm
Width	181.4 mm
Depth	26.0 mm
Net weight	570 g

Environment

Environmental characteristic	Weatherproof
------------------------------	--------------

IP degree of protection	IP44
Ambient air temperature for operation	-30...45 °C

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins