Product data sheet Characteristics

IMT47223

Mureva lights, Floodlight 200W, IP65 230V



Main

Mureva	
Mureva lights	
Floodlight	
Lamp	
Ware-houses and parking garages Residential Media device support Public areas Secure lighting Stadiums and arenas	those and independent
	Mureva lights Floodlight Lamp Ware-houses and parking garages Residential Media device support Public areas Secure lighting

Complementary

Complementary		2
Type of installation	Outdoor	
Total system power	200 W	
Light source	LED	
[Ue] rated operational voltage	230 V AC	:: :::::::::::::::::::::::::::::::::::
Power factor	0.9	
Colour rendering index	Ra=80	
Luminous flux	20000 lm	
Bulb lifespan	50000 h	2.
Colour temperature	6500 K	
Colour	Black	<u> </u>
Provided equipment	Sensor	
Beam angle	110 °	
Shape	Rectangular	
Height	342.0 mm	7
Width	278.0 mm	
Depth	61.0 mm	
Net weight	4.9 kg	

Environment

Environmental characteristic	Weatherproof	
------------------------------	--------------	--

IP degree of protection	IP65
Ambient air temperature for operation	-3045 °C

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins