

# Product datasheet

Specifications



## Manual transfer switch, GoPact MTS 200, 4 poles, 200A, 415VAC 50/60Hz, extended rotary handle, open transition

GM20D4N2004BEE

### Main

Range of product	GoPact MTS
Product or component type	Manual transfer switch
Product name	GoPact MTS 200
Device application	Change source of supply
Frame size	200
Suitability for isolation	Yes conforming to IEC 60947-3
Transfer switch class	PC
Poles description	4P
[Ie] rated operational current	AC-21A: 200 A conforming to IEC 60947-3 AC-22A: 200 A conforming to IEC 60947-3 AC-23A: 200 A conforming to IEC 60947-3 AC-31B: 200 A conforming to IEC 60947-6-1 AC-32B: 200 A conforming to IEC 60947-6-1
[Ith] conventional free air thermal current	200 A at 40 °C
[Ithe] conventional enclosed thermal current	200 A (40 °C)
Rated operational power in W	85 kW AC-23A conforming to IEC 60947-3
[Ue] rated operational voltage	415 V AC 50/60 Hz
Breaking capacity	1600 A AC-23A
Rated making capacity	2000 A AC-23A
Control type	Extended rotary handle
Operating mode	Manual
Contact position indicator	Yes
Mechanical interlocking	With mechanical interlocking
Locking options description	Padlocking in OFF position 1 to 3 padlocks

### Complementary

[Ui] rated insulation voltage	1000 V AC
[Uimp] rated impulse withstand voltage	12 kV
[Icm] rated short-circuit making capacity	14 kA peak

<b>[Icw] rated short-time withstand current</b>	8 kA during 1 s conforming to IEC 60947-4-3 18 kA during 0.2 s conforming to IEC 60947-4-3 10 kA during 0.1 s conforming to IEC 60947-6-1
<b>Number of contact position</b>	3
<b>Mounting mode</b>	Fixed
<b>Mounting support</b>	Backplate
<b>Connections - terminals</b>	1 cable with lug wire size 150 mm <sup>2</sup>
<b>Tightening torque</b>	10 N.m
<b>Mechanical durability</b>	16000 cycles
<b>Electrical durability</b>	1000 cycles 415 V
<b>Width</b>	210 mm
<b>Height</b>	211 mm
<b>Depth</b>	154 mm without handle: 267 mm with handle:
<b>Product weight</b>	4 kg
<b>Standards</b>	IEC 60947-3 IEC 60947-6-1
<b>Product certifications</b>	IECEE CB Scheme

## Environment

<b>Electrical shock protection class</b>	Class II
<b>IP degree of protection</b>	IP54 front face conforming to IEC 60529
<b>Pollution degree</b>	3 conforming to IEC 60664-1
<b>Ambient air temperature for operation</b>	-5...55 °C
<b>Temperature derating table</b>	40 °C ( 200 A ) 45 °C ( 200 A ) 50 °C ( 200 A ) 55 °C ( 190 A )
<b>Ambient air temperature for storage</b>	-25...85 °C
<b>Operating altitude</b>	2000 m 100 % of In 3000 m 96 % of In 4000 m 93 % of In 5000 m 89 % of In

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	33.3 cm
<b>Package 1 Width</b>	22.6 cm
<b>Package 1 Length</b>	26 cm
<b>Package 1 Weight</b>	6.7 kg
<b>Unit Type of Package 2</b>	P06
<b>Number of Units in Package 2</b>	6
<b>Package 2 Height</b>	88.4 cm
<b>Package 2 Width</b>	60 cm
<b>Package 2 Length</b>	80 cm
<b>Package 2 Weight</b>	267.6 kg

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
<b>RoHS exemption information</b>	Yes
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
<b>PVC free</b>	Yes

### Recommended replacement(s)