

# Product datasheet

Specifications



## MX shunt trip, GoPact MCCB 200/250, 240VAC 50/60Hz

G20-25SHT240AC

### Main

Range of product	GoPact MCCB
Product or component type	Voltage release
Device short name	MX
Device application	Control
Range compatibility	GoPact (GoPact MCCB 200) GoPact (GoPact MCCB 250)
Voltage release type	Shunt trip
[Uc] control circuit voltage	240 V AC 50/60 Hz

### Complementary

Threshold tripping voltage	0.7...1.1 Un opening
Max supply pick-up power consumption	5 VA
Response time	25 ms

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	8.5 cm
Package 1 Length	4.8 cm
Package 1 Weight	0.1 kg

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a>
RoHS exemption information	<a href="#">Yes</a>

**WEEE** The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---

PVC free

Yes

Recommended replacement(s)