



Product designation	MODULAR CONTACTOR
Product type designation	CN
Operating voltage type	AC/DC
Number of poles	4
Number of DIN modules	3

Electrical features

IEC Conventional free air thermal current I _{th}	A	40
Operational current AC1 and AC-7a ≤400V	A	40
Operational current AC3 and AC-7b ≤400V	A	22
Rated insulation voltage U _i IEC/EN	V	440
Rated impulse withstand voltage U _{imp}	kV	4
Minimum switching capacity		≥17V ≥50mA
Power dissipation per pole (average value) I _{th}	W	4

Control circuit

Auxiliary rated supply voltage U _s		220VAC/VDC
Auxiliary contacts	NO	Nr. 3
	NC	Nr. 1

Average coil consumption ≤20°C	in-rush	W	5
	holding	W	5

Operating voltage	pick-up	min	%U _s	85
		max	%U _s	110
	drop-out	min	%U _s	20
		max	%U _s	75

Operating times

Average time	Closing NO	min	ms	15
		max	ms	20
	Opening NO	min	ms	35
		max	ms	45

Operations

Mechanical life	cycles	3000000
Electrical life AC3	cycles	150000
Electrical life AC1	cycles	100000

Ambient conditions

Operating temperature	min	°C	-15
	max	°C	55

Storage temperature

min	°C	-30
max	°C	80

Max altitude

m	2000
---	------

Mechanical features

Fixing

DIN rail 35mm

Tightening torque for coil terminal

max	Nm	0.6
max	lbin	0.6

Tightening torque for terminals

max	Nm	2
max	lbin	1.48

Conductor section

Coil terminal

min	mm ²	1
max	mm ²	2.5

Power terminal

min	mm ²	1.5
max	mm ²	16

Terminals tool

PZ2

Weight

g 425

Resistance & Protection


Frontal IP degree

IP20


Pollution degree

3

Dimensions [mm (in)]



Wiring diagrams



Certifications and compliance

Compliance

IEC/EN 60947-1

IEC/EN 60947-4-1

IEC/EN 60947-5-1

IEC/EN 61095

Certificates

EAC

ETIM classification

ETIM 8.0

EC000066 -
Power contactor,
AC switching