



### Main

Range of product	EOCR
Device short name	EOCR-3D420
Product or component type	Protection relay
Product specific application	Overcurrent protection
Analogue output range	4...20 mA
Network type	AC
Network frequency	50...60 Hz
Protection adjustment range	0.5...10 A

### Complementary

Short-circuit and overload protection	By 4 A gG fuse
Display type	7 segments LED
Power consumption per relay	3 W
Height	71 mm
Width	70 mm
Depth	68 mm
Net weight	0.325 kg

### Environment

Standards	IEC 60947-4-1
Ambient air temperature for storage	-30...80 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	160 g
Package 1 Height	5.9 cm

Package 1 width	8.2 cm
Package 1 Length	7.9 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes