



### Main

Range of product	EOCR
Device short name	EOCR-3D420
Product or component type	Protection relay
Product specific application	Overcurrent protection
Analogue output range	4...20 mA
Network type	AC
Network frequency	50...60 Hz
Protection adjustment range	0.5...10 A

### Complementary

Short-circuit and overload protection	By 4 A gG fuse
Display type	7 segments LED
Power consumption per relay	3 W
Height	71 mm
Width	70 mm
Depth	68 mm
Net weight	0.325 kg

### Environment

Standards	IEC 60947-4-1
Ambient air temperature for storage	-30...80 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	221.6 g
Package 1 Height	9.5 cm
Package 1 width	6.3 cm
Package 1 Length	5.7 cm

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins