


# SLP-275 V/1+1

pluggable module, visual fault signalling, module locking


- combination of varistor surge arrester and encapsulated spark gap, connected in the 1+1 mode
- installation to LV installations, especially to sub-distribution boards in TT and also TN-S systems
- for protection of the installations and equipments against impact of induced overvoltages during a lightning strike or switching overvoltages



Product dimensions



Basic circuit diagram



## Technical parameters

Parameter name	Parameter value
Type of SPD	T2
Mounting	DIN rail 35 mm
Nominal voltage	$U_n$ 230 V AC
Maximum operating voltage L-N	$U_c$ 275.00 V AC
Maximum operating voltage N-PE	$U_c$ 255.00 V AC
Type of network	TT
Maximum overcurrent protection	160 A gL/gG
Short-circuit current rating	$I_{SCCR}$ 50.0 kA
Nominal discharge current (8/20 $\mu$ s) L-N	$I_n$ 20.00 kA
Nominal discharge current (8/20 $\mu$ s) N-PE	$I_n$ 20.00 kA
Maximum discharge current (8/20 $\mu$ s) L-N	$I_{max}$ 40.00 kA
Maximum discharge current (8/20 $\mu$ s) N-PE	$I_{max}$ 40.00 kA
Voltage protection level mode L-N	$U_p$ 1.35 kV
Voltage protection level mode L-PE	$U_p$ 1.50 kV

Voltage protection level mode N-PE	$U_p$	1.50 kV
Voltage protection level at 5 kA L-N	$U_p$	0.90 kV
Ability to independently switch off the following current N-PE	$I_{fi}$	0.1 kA
Response time L-N	$t_a$	25 ns
Response time N-PE	$t_a$	100 ns
TOV 5 s L-N		335 V
TOV characteristic (TOV 5 s)		withstand
TOV 120 min L-N		440 V
TOV characteristic (120 min)		safe failure
TOV 200 ms L-PE		1 455 V
TOV 200 ms N-PE		1 200 V
TOV characteristic (TOV 200 ms)		withstand
Cross-section of connected conductors solid (min)		1.00 mm <sup>2</sup>
Cross-section of connected conductors solid (max)		35.00 mm <sup>2</sup>
Cross-section of connected conductors stranded (min)		1.00 mm <sup>2</sup>
Cross-section of connected conductors stranded (max)		25.00 mm <sup>2</sup>
Fault indication L-N		red indication field
Fault indication N-PE		no
Degree of protection		IP 20
Range of ambient temperatures (min/max)		-40 / 80 °C
Humidity		5 - 95 %
According to standard		EN 61643-11:2012, IEC 61643-11:2011
ETIM Class		EC000941
Plug module		SLP-275 V/0 SLP-NPE V/0
Customs tariff number		85363030
EAN		8595090519485