



Figure similar

SIMATIC S7-300, Analog output SM 332, isolated, 2 AO, U/I; resolution 11/12 bits, 20-pole, Removing/inserting with active backplane bus possible

Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>Reverse polarity protection</li> </ul>	Yes
Input current	
from load voltage L+ (without load), max.	135 mA
from backplane bus 5 V DC, max.	60 mA
Power loss	
Power loss, typ.	3 W
Analog outputs	
Number of analog outputs	2
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	25 mA
Current output, no-load voltage, max.	18 V
Output ranges, voltage	
<ul style="list-style-type: none"> <li>0 to 10 V</li> </ul>	Yes
<ul style="list-style-type: none"> <li>1 V to 5 V</li> </ul>	Yes
<ul style="list-style-type: none"> <li>-10 V to +10 V</li> </ul>	Yes
Output ranges, current	
<ul style="list-style-type: none"> <li>0 to 20 mA</li> </ul>	Yes
<ul style="list-style-type: none"> <li>-20 mA to +20 mA</li> </ul>	Yes
<ul style="list-style-type: none"> <li>4 mA to 20 mA</li> </ul>	Yes
Load impedance (in rated range of output)	
<ul style="list-style-type: none"> <li>with voltage outputs, min.</li> </ul>	1 k $\Omega$
<ul style="list-style-type: none"> <li>with voltage outputs, capacitive load, max.</li> </ul>	1 $\mu$ F
<ul style="list-style-type: none"> <li>with current outputs, max.</li> </ul>	500 $\Omega$
<ul style="list-style-type: none"> <li>with current outputs, inductive load, max.</li> </ul>	10 mH
Cable length	
<ul style="list-style-type: none"> <li>shielded, max.</li> </ul>	200 m
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> <li>Resolution with overrange (bit including sign), max.</li> </ul>	12 bit; $\pm 10$ V, $\pm 20$ mA, 4 mA to 20 mA, 1 V to 5 V: 11 bit + sign; 0 V to 10 V, 0 mA to 20 mA: 12 bit
<ul style="list-style-type: none"> <li>Conversion time (per channel)</li> </ul>	0.8 ms
Settling time	
<ul style="list-style-type: none"> <li>for resistive load</li> </ul>	0.2 ms
<ul style="list-style-type: none"> <li>for capacitive load</li> </ul>	3.3 ms
<ul style="list-style-type: none"> <li>for inductive load</li> </ul>	0.5 ms; 0.5 ms (1 mH); 3.3 ms (10 mH)

Errors/accuracies	
Operational error limit in overall temperature range	
• Voltage, relative to output range, (+/-)	0.5 %
• Current, relative to output range, (+/-)	0.6 %
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to output range, (+/-)	0.4 %
• Current, relative to output range, (+/-)	0.5 %
Interrupts/diagnostics/status information	
Diagnostics function	Yes; Parameterizable
Alarms	
• Diagnostic alarm	Yes; Parameterizable
Diagnoses	
• Diagnostic information readable	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
Potential separation	
Potential separation analog outputs	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes
• between the channels and the power supply of the electronics	Yes
Isolation	
Isolation tested with	500 V DC
connection method / header	
required front connector	20-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	117 mm
Weights	
Weight, approx.	220 g
<b>last modified:</b>	1/17/2021 