



Figure similar

SIMATIC S7-300, Digital output SM 322, isolated, 8 DO (relay), 1x 40-pole, 24 V DC, 5 A or 230 V AC, 5 A, connectors with spring-loaded terminal can be used as of 6ES7392-1BM01-0AA0

Supply voltage	
Load voltage L+	
• Rated value (DC)	120 V
Load voltage L1	
• Rated value (AC)	230 V
Input current	
from supply voltage L+, max.	125 mA
from backplane bus 5 V DC, max.	40 mA
Power loss	
Power loss, typ.	3.2 W
Digital outputs	
Number of digital outputs	8; Relays
Short-circuit protection	No; to be provided externally
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	1 500 W; 230 V AC
• Low energy/fluorescent lamps with electronic control gear	10x 58 W
• Fluorescent tubes, conventionally compensated	1x 58 W
• Fluorescent tubes, uncompensated	10x 58 W
Output current	
• for signal "1" rated value	5 A
• for signal "1" minimum load current	5 mA
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes
Switching frequency	
• with resistive load, max.	2 Hz
• with inductive load, max.	0.5 Hz
• With inductive load (to IEC 60947-5-1, DC13/AC15), max.	0.5 Hz
• on lamp load, max.	2 Hz
• mechanical, max.	10 Hz
Total current of the outputs (per group)	
horizontal installation	
— up to 60 °C, max.	5 A
vertical installation	
— up to 40 °C, max.	5 A
Relay outputs	

<ul style="list-style-type: none"> <li>Rated supply voltage of relay coil L+ (DC)</li> <li>Contact connection (internal)</li> <li>Number of operating cycles, max.</li> </ul>	24 V No 300 000; 300 000 (24 V DC, at 2 A); 200 000 (120 V AC, at 3 A); 100 000 (230 V AC, at 3 A)
<b>Switching capacity of contacts</b>	
— with inductive load, max.	3 A; 3 A (230 V DC), 2 A (24 V AC)
— with resistive load, max.	8 A; 8 A (230 V DC), 5 A (24 V AC)
— Thermal continuous current, max.	8 A
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>shielded, max.</li> <li>unshielded, max.</li> </ul>	1 000 m 600 m
<b>Interrupts/diagnostics/status information</b>	
Alarms	No
Diagnostics function	No
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>Diagnostic alarm</li> </ul>	No
<b>Diagnoses</b>	
<ul style="list-style-type: none"> <li>Wire-break</li> <li>Short-circuit</li> <li>Fuse blown</li> <li>missing load voltage</li> </ul>	No No No No
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>Rated load voltage PWR (green)</li> <li>Fuse OK FSG (green)</li> <li>Status indicator digital output (green)</li> </ul>	No No Yes
<b>Potential separation</b>	
<b>Potential separation digital outputs</b>	
<ul style="list-style-type: none"> <li>between the channels</li> <li>between the channels, in groups of</li> <li>between the channels and backplane bus</li> </ul>	Yes 1 Yes; Optocoupler
<b>Isolation</b>	
Isolation tested with	2 000 V AC
<b>connection method / header</b>	
required front connector	40-pin
<b>Dimensions</b>	
Width	40 mm
Height	125 mm
Depth	120 mm
<b>Weights</b>	
Weight, approx.	320 g
<b>last modified:</b>	1/16/2021 