



SIMATIC S7-1500, digital output module DQ16x24...48VUC/125V DC/0.5A ST; 16 channels in groups of 1; 0.5 A per group; substitute value: observe derating the module supports the safety-oriented shutdown of load groups up to SILCL2 acc. to EN 62061:2005 + A2:2015, and Category 3 / PL d according to EN ISO 13849-1:2015. front connector (screw terminals or push-in) to be ordered separately

General information	
Product type designation	DQ 16x24 ... 48 V UC/125 V DC/0.5 A ST
HW functional status	FS02
Firmware version	V1.0.0
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>	No
<ul style="list-style-type: none"> <li>Prioritized startup</li> </ul>	Yes
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	V13 SP1 / -
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>	V5.5 SP3 / -
<ul style="list-style-type: none"> <li>PROFIBUS from GSD version/GSD revision</li> </ul>	V1.0 / V5.1
<ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>	V2.3 / -
Operating mode	
<ul style="list-style-type: none"> <li>DQ</li> </ul>	Yes
<ul style="list-style-type: none"> <li>DQ with energy-saving function</li> </ul>	No
<ul style="list-style-type: none"> <li>PWM</li> </ul>	No
<ul style="list-style-type: none"> <li>Cam control (switching at comparison values)</li> </ul>	No
<ul style="list-style-type: none"> <li>Oversampling</li> </ul>	No
<ul style="list-style-type: none"> <li>MSO</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Integrated operating cycle counter</li> </ul>	No
output voltage / header	
Rated value (DC)	24 V; 48 V, 125 V
Rated value (AC)	24 V; 48 V (50 - 60 Hz)
Power	
Power available from the backplane bus	2 W
Power loss	
Power loss, typ.	3.8 W
Digital outputs	
Type of digital output	Transistor
Number of digital outputs	16
Current-sinking	Yes
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
Limitation of inductive shutdown voltage to	200 V (suppressor diode)
Controlling a digital input	Yes
Switching capacity of the outputs	

<ul style="list-style-type: none"> <li>with resistive load, max.</li> <li>on lamp load, max.</li> </ul>	0.5 A 40 W; At 125 V DC, 10 W at 48 V UC, 5 W at 24 V UC
<b>Output voltage</b>	
<ul style="list-style-type: none"> <li>for signal "1", min.</li> </ul>	L+ (-1.0 V)
<b>Output current</b>	
<ul style="list-style-type: none"> <li>for signal "1" rated value</li> <li>for signal "1" permissible range, max.</li> </ul>	0.5 A 0.6 A
<b>Output delay with resistive load</b>	
<ul style="list-style-type: none"> <li>"0" to "1", max.</li> <li>"1" to "0", max.</li> </ul>	5 ms 5 ms
<b>Parallel switching of two outputs</b>	
<ul style="list-style-type: none"> <li>for logic links</li> <li>for uprating</li> <li>for redundant control of a load</li> </ul>	Yes No Yes
<b>Switching frequency</b>	
<ul style="list-style-type: none"> <li>with resistive load, max.</li> <li>with inductive load, max.</li> <li>on lamp load, max.</li> </ul>	25 Hz 0.5 Hz 10 Hz
<b>Total current of the outputs</b>	
<ul style="list-style-type: none"> <li>Current per channel, max.</li> <li>Current per group, max.</li> <li>Current per module, max.</li> </ul>	0.5 A 0.5 A 8 A
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>shielded, max.</li> <li>unshielded, max.</li> </ul>	1 000 m 600 m
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	No
Substitute values connectable	Yes
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>Diagnostic alarm</li> <li>Maintenance interrupt</li> </ul>	No No
<b>Diagnoses</b>	
<ul style="list-style-type: none"> <li>Monitoring the supply voltage</li> <li>Wire-break</li> <li>Short-circuit</li> </ul>	No No No
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>RUN LED</li> <li>ERROR LED</li> <li>Monitoring of the supply voltage (PWR-LED)</li> <li>Channel status display</li> <li>for channel diagnostics</li> <li>for module diagnostics</li> </ul>	Yes; green LED Yes; red LED No Yes; green LED No Yes; red LED
<b>Potential separation</b>	
<b>Potential separation channels</b>	
<ul style="list-style-type: none"> <li>between the channels</li> <li>between the channels, in groups of</li> <li>between the channels and backplane bus</li> </ul>	Yes 1 Yes
<b>Permissible potential difference</b>	
between different circuits	125 V DC/48 V AC
<b>Isolation</b>	
Isolation tested with	2 000 V DC
<b>Standards, approvals, certificates</b>	
Suitable for safety functions	No
Suitable for safety-related tripping of standard modules	Yes; From FS02
<b>Highest safety class achievable for safety-related tripping of standard modules</b>	
<ul style="list-style-type: none"> <li>Performance level according to ISO 13849-1</li> <li>Category according to ISO 13849-1</li> <li>SILCL according to IEC 62061</li> </ul>	PL d Cat. 3 SILCL 2
<b>Ambient conditions</b>	

Ambient temperature during operation	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	40 °C
Dimensions	
Width	35 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	230 g
<b>last modified:</b>	1/16/2021 